

# SAFETY DATA SHEET

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name or designation of the mixture	BLUEBERRY JAM FLAVOR N&A TYPE
Registration number	-
Synonyms	None.
Product code	CA1424
Issue date	24-November-2015
Version number	05
Revision date	04-October-2016
Supersedes date	29-June-2016

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Use in accordance with supplier's recommendations.
Uses advised against	No other uses are advised.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

Company name	Capella Flavors, Inc.	
Address	6155 Corte Del Cedro Carlsbad, CA 92011 United States	
Division		
Telephone	Office	760 650-0200
	Fax	n/a
e-mail	customerservice@capellaflavors.com	
Contact person	Not available.	

1.4. Emergency telephone number	CHEMTREC	800-424-9300
	INTERNATIONAL	703-741-5500

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Directive 67/548/EEC or 1999/45/EC as amended

This preparation does not meet the criteria for classification according to Directive 1999/45/EC as amended.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.
--	------------	---

#### Hazard summary

Physical hazards	Not classified for physical hazards.
Health hazards	Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse health effects.
Environmental hazards	Not classified for hazards to the environment.
Specific hazards	None known.
Main symptoms	Direct contact with eyes may cause temporary irritation.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms	None.
Signal word	None.
Hazard statements	
H412	Harmful to aquatic life with long lasting effects.

## Precautionary statements

### Prevention

P273 Avoid release to the environment.

### Response

Wash hands after handling.

### Storage

Store away from incompatible materials.

### Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Supplemental label information** 1,99 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. EUH208 - Contains HEXENOL CIS-3 #86 NOM, DAMASCENONE TOTAL #186. May produce an allergic reaction.

**2.3. Other hazards** None known.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
ETHYL ALCOHOL 190 PROOF NAT NFI	1-<3	64-17-5 200-578-6	-	603-002-00-5	
<b>Classification:</b>	<b>DSD:</b> F;R11, Xi;R36				
	<b>CLP:</b> Flam. Liq. 2;H225, Eye Irrit. 2;H319, Aquatic Chronic 2;H411				
TRADE SECRET	<1	Proprietary	-	-	
<b>Classification:</b>	<b>DSD:</b> Xn;R21, Xi;R38, R43				
	<b>CLP:</b> Acute Tox. 4;H312, Skin Irrit. 2;H315, Skin Sens. 1;H317				
TRADE SECRET	< 0,2	Proprietary	-	-	
<b>Classification:</b>	<b>DSD:</b> C;R34, Xn;R21, R52/53				
	<b>CLP:</b> Acute Tox. 3;H311, Skin Corr. 1B;H314, Eye Dam. 1;H318, Aquatic Chronic 3;H412				
TRADE SECRET	< 0,2	Proprietary	-	-	
<b>Classification:</b>	<b>DSD:</b> R43, N;R51/53				
	<b>CLP:</b> Skin Sens. 1;H317, Aquatic Chronic 2;H411				

Other components below reportable levels 90 - 100

#### List of abbreviations and symbols that may be used above

CLP: Regulation No. 1272/2008.

DSD: Directive 67/548/EEC.

M: M-factor

vPvB: very persistent and very bioaccumulative substance.

PBT: persistent, bioaccumulative and toxic substance.

#: This substance has been assigned Community workplace exposure limit(s).

**Composition comments** The full text for all R- and H-phrases is displayed in section 16.

## SECTION 4: First aid measures

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

### 4.1. Description of first aid measures

**Inhalation** Move to fresh air. Call a physician if symptoms develop or persist.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

**4.2. Most important symptoms and effects, both acute and delayed** Direct contact with eyes may cause temporary irritation.

4.3. Indication of any immediate medical attention and special treatment needed  
Treat symptomatically.

## SECTION 5: Firefighting measures

**General fire hazards** No unusual fire or explosion hazards noted.

**5.1. Extinguishing media**

**Suitable extinguishing media** Powder. Alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** During fire, gases hazardous to health may be formed.

**5.3. Advice for firefighters**

**Special protective equipment for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Special fire fighting procedures** Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

**For non-emergency personnel** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8.

**For emergency responders** Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

**6.2. Environmental precautions** Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

**6.3. Methods and material for containment and cleaning up**

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Use water spray to reduce vapours or divert vapour cloud drift. Absorb in vermiculite, dry sand or earth and place into containers. Prevent product from entering drains. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use.

**6.4. Reference to other sections** For personal protection, see section 8. For waste disposal, see section 13 of the SDS.

## SECTION 7: Handling and storage

**7.1. Precautions for safe handling** Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

**7.2. Conditions for safe storage, including any incompatibilities** Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

**7.3. Specific end use(s)** Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	Ceiling	3800 mg/m <sup>3</sup>
	MAK	2000 ppm
		1900 mg/m <sup>3</sup>
		1000 ppm

**Belgium. Exposure Limit Values.**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1907 mg/m3
		1000 ppm

**Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1000 mg/m3
TRADE SECRET	TWA	5 mg/m3

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	MAC	1900 mg/m3
		1000 ppm
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	MAC	10 mg/m3
		150 ppm

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	Ceiling	3000 mg/m3
	TWA	1000 mg/m3

**Denmark. Exposure Limit Values**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TLV	1900 mg/m3
		1000 ppm

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1900 mg/m3
		1000 ppm
	TWA	1000 mg/m3 500 ppm

**Finland. Workplace Exposure Limits**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	2500 mg/m3
		1300 ppm
	TWA	1900 mg/m3 1000 ppm

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	VLE	9500 mg/m3
		5000 ppm
	VME	1900 mg/m3 1000 ppm

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	960 mg/m <sup>3</sup>
		500 ppm

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	AGW	960 mg/m <sup>3</sup>
		500 ppm

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1900 mg/m <sup>3</sup>
		1000 ppm

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	7600 mg/m <sup>3</sup>
	TWA	1900 mg/m <sup>3</sup>

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1900 mg/m <sup>3</sup>
		1000 ppm

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1000 ppm	
	PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	TWA	470 mg/m <sup>3</sup>
		10 mg/m <sup>3</sup> 150 ppm	

**Italy. Occupational Exposure Limits**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1000 ppm

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1000 mg/m <sup>3</sup>
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	TWA	7 mg/m <sup>3</sup>
TRADE SECRET	TWA	5 mg/m <sup>3</sup>

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1900 mg/m <sup>3</sup>
		1000 ppm
	TWA	1000 mg/m <sup>3</sup> 500 ppm

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6) TRADE SECRET	TWA	7 mg/m3
	TWA	5 mg/m3

**Netherlands. OELs (binding)**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1900 mg/m3
	TWA	260 mg/m3

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TLV	950 mg/m3
		500 ppm
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	TLV	79 mg/m3
		25 ppm

**Poland. MACs. Minister of Labour and Social Policy Regarding Maximum Allowable Concentrations and Intensities in Working Environment**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1900 mg/m3

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1000 ppm

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	9500 mg/m3
	TWA	5000 ppm 1900 mg/m3 1000 ppm

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1920 mg/m3
	TWA	1000 ppm 960 mg/m3 500 ppm

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1900 mg/m3
		1000 ppm

**Spain. Occupational Exposure Limits**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1910 mg/m3
		1000 ppm

**Sweden. Occupational Exposure Limit Values**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1900 mg/m3
	TWA	1000 ppm
		1000 mg/m3 500 ppm

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	STEL	1920 mg/m3
	TWA	1000 ppm
		960 mg/m3 500 ppm

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value	Form
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)	TWA	1920 mg/m3	
		1000 ppm	
PROPYLENE GLYCOL NOM NFI (CAS 57-55-6)	TWA	474 mg/m3	Total vapour and particulates.
		10 mg/m3	Particulate.
		150 ppm	Total vapour and particulates.

**Biological limit values** No biological exposure limits noted for the ingredient(s).

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no-effect level (DNEL)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**8.2. Exposure controls**

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information** Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** Wear safety glasses with side shields (or goggles).

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves. Suitable gloves can be recommended by the glove supplier.

**- Other** Wear suitable protective clothing.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

**Environmental exposure controls** Inform appropriate managerial or supervisory personnel of all environmental releases.

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties****Appearance**

**Physical state** Liquid.  
**Form** Liquid.  
**Colour** Not available.

<b>Odour</b>	Not available.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	-59 °C (-74,2 °F) estimated
<b>Initial boiling point and boiling range</b>	188,2 °C (370,76 °F) estimated
<b>Flash point</b>	65,6 °C (150,0 °F)
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Vapour pressure</b>	0,17 hPa estimated
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Solubility (other)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	371,11 °C (700 °F) estimated
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not explosive.
<b>Oxidizing properties</b>	Not oxidizing.
<b>9.2. Other information</b>	
<b>Refractive index</b>	1,4148 - 1,4448
<b>Specific gravity</b>	1,01 - 1,04

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Avoid temperatures exceeding the flash point. Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Strong oxidising agents.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

<b>General information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
<b>Information on likely routes of exposure</b>	
<b>Inhalation</b>	May cause allergy or asthma symptoms or breathing difficulties if inhaled. Prolonged inhalation may be harmful.
<b>Skin contact</b>	May cause an allergic skin reaction.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
<b>Symptoms</b>	Exposure may cause temporary irritation, redness, or discomfort.
<b>11.1. Information on toxicological effects</b>	
<b>Acute toxicity</b>	No data available.
<b>Skin corrosion/irritation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Serious eye damage/eye irritation</b>	Due to partial or complete lack of data the classification is not possible.

<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Skin sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Carcinogenicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Reproductive toxicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - single exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Aspiration hazard</b>	Due to partial or complete lack of data the classification is not possible.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	May cause allergic respiratory and skin reactions.

## SECTION 12: Ecological information

<b>12.1. Toxicity</b>	Harmful to aquatic life with long lasting effects.
<b>12.2. Persistence and degradability</b>	No data is available on the degradability of this product.
<b>12.3. Bioaccumulative potential</b>	
<b>Partition coefficient n-octanol/water (log Kow)</b>	
ETHYL ALCOHOL 190 PROOF NAT NFI	-0,31
TRADE SECRET	1,88
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not available.
<b>12.6. Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

Not regulated as dangerous goods.

### RID

Not regulated as dangerous goods.

### ADN

Not regulated as dangerous goods.

### IATA

Not regulated as dangerous goods.

### IMDG

Not regulated as dangerous goods.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not established.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I, as amended  
Not listed.
- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex II, as amended  
Not listed.
- Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended  
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 1 as amended  
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 2 as amended  
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex I, part 3 as amended  
Not listed.
- Regulation (EC) No. 689/2008 concerning the export and import of dangerous chemicals, Annex V as amended  
Not listed.
- Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended  
Not listed.
- Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA  
Not listed.

#### Authorisations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended  
Not listed.
- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended  
Not listed.

#### Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended  
Not listed.
- Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended  
Not listed.
- Directive 92/85/EEC: on the safety and health of pregnant workers and workers who have recently given birth or are breastfeeding, as amended  
Not listed.

#### Other EU regulations

- Directive 2012/18/EU on major accident hazards involving dangerous substances  
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)
- Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work, as amended  
ETHYL ALCOHOL 190 PROOF NAT NFI (CAS 64-17-5)
- Directive 94/33/EC on the protection of young people at work, as amended  
Not listed.

#### Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006.

#### National regulations

Follow national regulation for work with chemical agents.

### 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

## SECTION 16: Other information

List of abbreviations Not available.

References Not available.

**Information on evaluation method leading to the classification of mixture**  
**Full text of any statements or R-phrases and H-statements under Sections 2 to 15**

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

R11 Highly flammable.  
R21 Harmful in contact with skin.  
R34 Causes burns.  
R36 Irritating to eyes.  
R38 Irritating to skin.  
R43 May cause sensitisation by skin contact.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
H225 Highly flammable liquid and vapour.  
H311 Toxic in contact with skin.  
H312 Harmful in contact with skin.  
H314 Causes severe skin burns and eye damage.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H318 Causes serious eye damage.  
H319 Causes serious eye irritation.  
H411 Toxic to aquatic life with long lasting effects.  
H412 Harmful to aquatic life with long lasting effects.  
None.

**Revision information**

**Training information**

**Disclaimer**

Follow training instructions when handling this material.

Capella Flavors, Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.